

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 1 of 11  
Print date: 27/12/2024

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: Modeling Grey Putty  
Product Code: 8022206  
UFI: XG10-H00S-400C-2VVE

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Painting, decoration of models and figures, decoration of objects.

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **AK Interactive S.L.**  
Address: Valsalado,2  
City: 26007 - LOGROÑO  
Province: LA RIOJA  
Telephone: +34 94 122 30 64  
E-mail: info@ak-interactive.com  
Web: www.ak-interactive.com

#### 1.4 Emergency telephone number: +34 94 122 30 64 (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.  
Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

**Warning**

Hazard statements:

H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...  
P321 Specific treatment (see ... on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P391 Collect spillage.  
P501 Dispose of contents/container to ...

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 2 of 11  
Print date: 27/12/2024

EUH statements:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Contains:

octhiline (ISO),2-octyl-2H-isothiazol-3-one

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

### 2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 7727-43-7 EC No: 231-784-4 Registration No: 01-2119491274-35-XXXX	[1] barium sulfate	25 - 50 %	-	-
Index No: 603-027-00-1 CAS No: 107-21-1 EC No: 203-473-3 Registration No: 01-2119456816-28-XXXX	[1] ethanediol, ethylene glycol	0 - 2.5 %	Acute Tox. 4, H302	-
Index No: 613-112-00-5 CAS No: 26530-20-1 EC No: 247-761-7 Registration No: 01-2120768921-45-XXXX	octhiline (ISO),2-octyl-2H-isothiazol-3-one	0.025 - 0.25 %	Acute Tox. 2, H330 - Acute Tox. 3, H311 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=100) - Aquatic Chronic 1, H410 (M=100) - Eye Dam. 1, H318 - Skin Corr. 1, H314 - Skin Sens. 1A, H317, EUH071	Skin Sens. 1A, H317: C ≥ 0,0015 % Dermal: ETA = 311 mg/kg bw (ATP 15) Inhalation: ETA = 0.27 mg/L (ATP 15) Oral: ETA = 125 mg/kg bw (ATP 15)
Index No: 613-088-00-6 CAS No: 2634-33-5 EC No: 220-120-9 Registration No: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	0 - 0.05 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Skin Sens. 1, H317: C ≥ 0,05 %

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 3 of 11  
Print date: 27/12/2024

CAS No: 55965-84-9 Registration No: 01-2120764691-48-XXXX	Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one	0.0025 - 0.025 %	Acute Tox. 2, H310 - Acute Tox. 2, H330 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=100) - Aquatic Chronic 1, H410 (M=100) - Eye Dam. 1, H318 - Skin Corr. 1C, H314 - Skin Sens. 1A, H317, EUH071	Skin Corr. 1C, H314: C ≥ 0,6 % Skin Irrit. 2, H315: 0,06 % ≤ C < 0,6 % Skin Sens. 1A, H317: C ≥ 0,002%
--	---	------------------	---	--

(\* ) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. If the person vomits, clear the respiratory tract. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

### SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

##### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 4 of 11  
Print date: 27/12/2024

### 5.2 Special hazards arising from the substance or mixture.

#### **Special risks.**

Exposure to combustion or decomposition products can be harmful to your health.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

#### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500

### 7.3 Specific end use(s).

Not available.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 5 of 11  
Print date: 27/12/2024

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
barium sulfate	7727-43-7	European Union [1]	Eight hours		0,5
			Short term		
ethanediol, ethylene glycol	107-21-1	European Union [1]	Eight hours	20 (skin)	52 (skin)
			Short term	40 (skin)	104 (skin)

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
barium sulfate CAS No: 7727-43-7 EC No: 231-784-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	10 (mg/m <sup>3</sup> )
ethanediol, ethylene glycol CAS No: 107-21-1 EC No: 203-473-3	DNEL (Workers)	Inhalation, Chronic, Local effects	35 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

#### 8.2 Exposure controls.

##### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	100 %		
<b>Uses:</b>	Painting, decoration of models and figures, decoration of objects.		
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Work gloves.		
Characteristics:	«CE» marking, category I.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Face shield.		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 6 of 11  
Print date: 27/12/2024

Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.
<b>Skin protection:</b>	
PPE:	Protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Color según indica la etiqueta o a la vista del producto.

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: > 60 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: 8-9 (100%)

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: Not applicable/Not available due to the nature/properties of the product

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

#### 9.2 Other information

Not applicable/Not available due to the nature/properties of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 7 of 11  
Print date: 27/12/2024

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.

### 11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

#### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
octhilionone (ISO),2-octyl-2H-isothiazol-3-one CAS No: 26530-20-1 EC No: 247-761-7	Oral	LD50	Rat	550 mg/kg
	Dermal	LD50	Mouse	690 mg/kg
	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 8 of 11  
Print date: 27/12/2024

### 11.2 Information on other hazards.

#### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
octhilonone (ISO),2-octyl-2H-isothiazol-3-one  CAS No: 26530-20-1 EC No: 247-761-7	Fish	LC50	Fish	0.154 mg/l (96 h) [1] [1] Office of Pesticide Programs 2000. Pesticide Ecotoxicity Database (Formerly: Environmental Effects Database (EEDB)). Environmental Fate and Effects Division, U.S.EPA, Washington, D.C.
	Aquatic invertebrates	EC50	Crustaceans	0.25 mg/l (48 h) [1] [1] Office of Pesticide Programs 2000. Pesticide Ecotoxicity Database (Formerly: Environmental Effects Database (EEDB)). Environmental Fate and Effects Division, U.S.EPA, Washington, D.C.
	Aquatic plants			

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethanediol, ethylene glycol CAS No: 107-21-1 EC No: 203-473-3	-1,36	-	-	Very low
octhilonone (ISO),2-octyl-2H-isothiazol-3-one CAS No: 26530-20-1 EC No: 247-761-7	2,45	19,21	-	Low

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1      Date of compilation: 27/12/2024

Page 9 of 11  
Print date: 27/12/2024

### 12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

### 14.1 UN number or ID number.

Transportation is not dangerous.

### 14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

### 14.3 Transport hazard class(es).

Transportation is not dangerous.

### 14.4 Packing group.

Transportation is not dangerous.

### 14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

### 14.6 Special precautions for user.

Transportation is not dangerous.

### 14.7 Maritime transport in bulk according to IMO instruments.

Not classified as hazardous for transport.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1 Date of compilation: 27/12/2024

Page 10 of 11  
Print date: 27/12/2024

### SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Complete text of the EUH phrases that appear in section 3:

EUH071	Corrosive to the respiratory tract.
--------	-------------------------------------

Classification codes:

Acute Tox. 2 : Acute toxicity (Dermal), Category 2  
Acute Tox. 2 : Acute toxicity (Inhalation), Category 2  
Acute Tox. 3 : Acute toxicity (Dermal), Category 3  
Acute Tox. 3 : Acute toxicity (Oral), Category 3  
Acute Tox. 4 : Acute toxicity (Oral), Category 4  
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1  
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1  
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2  
Eye Dam. 1 : Serious eye damage, Category 1  
Skin Corr. 1 : Skin Corrosive, Category 1  
Skin Corr. 1C : Skin Corrosive, Category 1C  
Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitiser, Category 1  
Skin Sens. 1A : Skin sensitiser, Category 1A

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
NOEC:	No observed effect concentration.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>  
<http://echa.europa.eu/>  
Regulation (EU) 2020/878.  
Regulation (EC) No 1907/2006.  
Regulation (EC) No 1272/2008.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 8022206-Modeling Grey Putty

Version 1      Date of compilation: 27/12/2024

Page 11 of 11  
Print date: 27/12/2024

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.