

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 1 of 13
Print date: 25/03/2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: AK140XY- Liquid Pigment AFV
Product Code: 80271ZK
UFI: 8M00-F03T-200E-FG1S

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Painting, decoration of models and figures, decoration of objects.

Uses advised against:

Children
Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **AK Interactive S.L.**
Address: Valsalado,2
City: 26007 - LOGROÑO
Province: LA RIOJA
Telephone: +34 94 122 30 64
E-mail: info@ak-interactive.com
Web: www.ak-interactive.com

1.4 Emergency telephone number: +34 94 122 30 64 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 3 : Flammable liquid and vapour.

STOT RE 1 : Causes damage to organs through prolonged or repeated exposure.

STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Danger

Hazard statements:

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 2 of 13
Print date: 25/03/2025

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

EUH statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains:

propan-2-ol, isopropyl alcohol, isopropanol
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 64742-82-1 Registration No: 01-2119458049-33-XXXX	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	25 - 75 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT RE 1, H372 - STOT SE 3, H336, EUH066	-
Index No: 603-117-00-0 CAS No: 67-63-0 EC No: 200-661-7 Registration No: 01-2119457558-25-XXXX	propan-2-ol, isopropyl alcohol, isopropanol	20 - 50 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 603-001-00-X CAS No: 67-56-1 EC No: 200-659-6 Registration No: 01-2119433307-44-XXXX	[1] methanol	0 - 3 %	Acute Tox. 3 *, H311 - Acute Tox. 3 *, H331 - Acute Tox. 3 *, H301 - Flam. Liq. 2, H225 - STOT SE 1, H370 **	STOT SE 1, H370: C ≥ 10 % STOT SE 2, H371: 3 % ≤ C < 10 %

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*, ** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 3 of 13
Print date: 25/03/2025

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Delayed effects may occur after the exposure to the product.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

Long-term chronic exposure may result in injury to certain organs or tissues.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 4 of 13
Print date: 25/03/2025

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500
P5c	FLAMMABLE LIQUIDS	5.000	50.000

7.3 Specific end use(s).

Not available.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 5 of 13
Print date: 25/03/2025

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
methanol	67-56-1	European Union [1]	Eight hours	200 (skin)	260 (skin)
			Short term		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	500 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	89 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	888 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	319 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	26 (mg/kg bw/day)
methanol CAS No: 67-56-1 EC No: 200-659-6	DNEL (Workers)	Inhalation, Chronic, Local effects	260 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Local effects	50 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	260 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	50 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	40 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	8 (mg/kg bw/day)
	DNEL (Workers)	Dermal, Short term, Systemic effects	40 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Short term, Systemic effects	8 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	aqua (freshwater)	140,9 (mg/L)
	aqua (marine water)	140,9 (mg/L)
	aqua (intermittent releases)	140,9 (mg/L)
	sediment (freshwater)	552 (mg/kg sediment dw)
	sediment (marine water)	552 (mg/kg sediment dw)
	Soil	28 (mg/kg soil dw)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 6 of 13
Print date: 25/03/2025

	STP	2251 (mg/L)
	oral (Hazard for predators)	160 (mg/kg food)
methanol CAS No: 67-56-1 EC No: 200-659-6	aqua (freshwater)	20,8 (mg/L)
	aqua (marine water)	2,08 (mg/L)
	aqua (intermittent releases)	1540 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	77 (mg/kg sediment dw)
	sediment (marine water)	7,7 (mg/kg sediment dw)
	soil	3,18 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Painting, decoration of models and figures, decoration of objects.		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Chemical protective clothing		
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.		
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 7 of 13
Print date: 25/03/2025

Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.
PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Color según indica la etiqueta o a la vista del producto.

Odour: Disolvente

Odour threshold: Not available

Melting point: Not available

Freezing point: Not applicable (Not relevant for this type of product)

Boiling point or initial boiling point and boiling range: >182 °C (Determination by use of the ebullimeter (ASTM D 1120-72 (1)))

Flammability: Not available due to the nature/properties of the product

Lower explosion limit: 0.60 (Determination of the explosion limits and the limiting oxygen concentration (LOC) for flammable gases and vapours. (UNE-EN 1839:2017))

Upper explosion limit: 6 (Determination of the explosion limits and the limiting oxygen concentration (LOC) for flammable gases and vapours. (UNE-EN 1839:2017))

Flash point: 23 °C

Auto-ignition temperature: 222 °C

Decomposition temperature: Not available due to the nature/properties of the product

pH: Not available (Substance/mixture is apolar/aprotic).

Kinematic viscosity: Not available due to the nature/properties of the product

Solubility: 0.01414 kg/m³

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): 5.52

Vapour pressure: 0.06 Pa

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: Not applicable/Not available due to the nature/properties of the product

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 8 of 13
Print date: 25/03/2025

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	Oral	LD50	Rat	5050 mg/kg bw [1] [1] Gigiena i Sanitariya. For English translation, see HYSAAV. Vol. 43(1), Pg. 8, 1978
	Dermal	LD50	Rabbit	12800 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 100, 1974
	Inhalation	LC50	Rat	>10000 ppm (6 h) [1] [1] OECD Guideline 403 (Acute Inhalation Toxicity), study report, 1991
methanol CAS No: 67-56-1 EC No: 200-659-6	Oral	LD50	Rat	5630 mg/kg bw [1] [1] Gigiena Truda i Professional'nye Zabolevaniya. Labor Hygiene and Occupational Diseases. Vol. 19(11), Pg. 27, 1975
	Dermal	LD50	Rabbit	15800 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 74, 1974
	Inhalation	LC50	Rat	83.9 mg/l (4 h) [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 74, 1974

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 9 of 13
Print date: 25/03/2025

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;
Product classified:
Specific target organ toxicity following a repeated exposure, Category 1: Causes damage to organs through prolonged or repeated exposure.

j) aspiration hazard;
Based on available data, the classification criteria are not met.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	Fish	LC50	Fish	9640 mg/l (96 h) [1] [1] Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (<i>Pimephales promelas</i>), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior, Superior, WI :414
	Aquatic invertebrates	LC50	Crustacean	1400 mg/l (48 h) [1] [1] Blackman, R.A.A. 1974. Toxicity of Oil-Sinking Agents. Mar.Pollut.Bull. 5:116-118
	Aquatic plants	Toxicity threshold	Scenedesmus quadricauda	1800 mg/L (7 d) [1] [1] Comparison of the Toxicity Thresholds of Water Pollutants to Bacteria, Algae, and Protozoa in the Cell Multiplication Inhibition Test, Water Research Vol. 14. pp. 231 to 241
methanol	Fish	LC50	Trachinotus carolinus	10112 mg/L (24 h) [1] [1] Baltz, D. M. et al., Transactions of the American Fisheries Society 134: 730-740, 2005
	Aquatic invertebrates	EC50	Daphnia magna	20803 mg/L (24 h) [1] [1] Environmental Toxicology and Chemistry 14(12): 2085-2088, 1995
	Aquatic plants	EC50	Selenastrum capricornutum	22000 mg/L (96 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 10 of 13
Print date: 25/03/2025

CAS No: 67-56-1	EC No: 200-659-6	[1] Ecotoxicology and Environmental Safety 71: 166-1711, 2008
-----------------	------------------	---

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.
No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	0,05	-	-	Very low
methanol CAS No: 67-56-1 EC No: 200-659-6	-0,74	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.
No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 11 of 13
Print date: 25/03/2025

14.1 UN number or ID number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1263, PAINT, 3, PG III, (D/E)

IMDG: UN 1263, PAINT (HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)), 3, PG III, MARINE POLLUTANT

ICAO/IATA: UN 1263, PAINT, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

14.6 Special precautions for user.

Labels: 3



Hazard number: 30

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



80271ZK-AK140XY- Liquid Pigment AFV

Version 1 Date of compilation: 25/03/2025

Page 12 of 13
Print date: 25/03/2025

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Complete text of the EUH phrases that appear in section 3:

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Classification codes:

Acute Tox. 3 : Acute toxicity (Dermal), Category 3
Acute Tox. 3 : Acute toxicity (Inhalation), Category 3
Acute Tox. 3 : Acute toxicity (Oral), Category 3
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1
STOT SE 1 : Specific target organ toxicity following a single exposure, Category 1
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR:	Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organization.
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
NOEC:	No observed effect concentration.
PNEC:	Predicted No Effect Concentration, concentration of the substance below which adverse effects are

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

80271ZK-AK140XY- Liquid Pigment AFV



Version 1 Date of compilation: 25/03/2025

Page 13 of 13
Print date: 25/03/2025

RID: not expected in the environmental compartment.
Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.